

SGP溶協・高炉

呼び径		外径 (mm)	溶協		高炉	
A	B (インチ)		厚さ (mm)	在庫	厚さ (mm)	在庫
15	1/2	21.7	2.8	●	2.8	●
20	3/4	27.2	2.8	●	2.8	●
25	1	34.0	3.2	●	3.2	●
32	1 1/4	42.7	3.5	●	3.5	●
40	1 1/2	48.6	3.5	●	3.5	●
50	2	60.5	3.8	●	3.8	●
65	2 1/2	76.3	4.2	●	4.2	●
80	3	89.1	4.2	●	4.2	●
90	3 1/2	101.6	4.2	●	4.2	●
100	4	114.3	4.5	●	4.5	●
125	5	139.8	4.5	●	4.5	●
150	6	165.2	5.0	●	5.0	●
175		190.7	5.3	●	5.3	●
200	8	216.3	5.8	●	5.8	●
225		241.8			6.2	●
250	10	267.4	6.6	●	6.6	●
300	12	318.5	6.9	●	6.9	●
350	14	355.6	7.9	●	7.9	●
400	16	406.4	7.9	●	7.9	●
450	18	457.2			7.9	●
500	20	508.0			7.9	●

※ 溶協 6A、8A、10Aは、取り寄せ材になります。

STPG (S) ・ (E)

呼び径		外径	Sch40			Sch80		
A	B (インチ)	(mm)	厚さ (mm)	在庫		厚さ (mm)	在庫	
				S	E		S	E
15	1/2	21.7	2.8	●	●	3.7	●	●
20	3/4	27.2	2.9	●	●	3.9	●	●
25	1	34.0	3.4	●	●	4.5	●	●
32	1 1/4	42.7	3.6	●	●	4.9	●	●
40	1 1/2	48.6	3.7	●	●	5.1	●	●
50	2	60.5	3.9	●	●	5.5	●	●
65	2 1/2	76.3	5.2	●	●	7.0	●	●
80	3	89.1	5.5	●	●	7.6	●	●
90	3 1/2	101.6	5.7	●	●	8.1	●	●
100	4	114.3	6.0	●	●	8.6	●	●
125	5	139.8	6.6	●	●	9.5	●	●
150	6	165.2	7.1	●	●	11.0	●	●
200	8	216.3	8.2	●	●	12.7	●	●
250	10	267.4	9.3	●	●	15.1	●	●
300	12	318.5	10.3	●	●	17.4	●	●
350	14	355.6	11.1	●	●	19.0	●	●
400	16	406.4	12.7	●	●	21.4	●	●
450	18	457.2	14.3		●	23.8		●
500	20	508.0	15.1		●	26.2		●

アルミパイプA5052

42.0×7.0 (28.0)	52.0×7.0 (38.0)	52.0×8.0 (36.0)	62.0×7.0 (48.0)	62.0×10.0 (42.0)	69.0×6.0 (57.0)	72.0×7.0 (58.0)	72.0×10.0 (52.0)	77.0×7.0 (63.0)	80.0×7.0 (66.0)
82.0×6.0 (70.0)	82.0×7.0 (68.0)	82.0×8.0 (66.0)	82.0×10.0 (62.0)	83.0×8.0 (67.0)	87.0×7.0 (73.0)	89.0×7.0 (75.0)	92.0×5.0 (82.0)	92.0×7.0 (78.0)	92.0×10.0 (72.0)
102.0×6.0 (90.0)	102.0×7.0 (88.0)	102.0×8.0 (86.0)	102.0×10.0 (82.0)	102.0×12.0 (78.0)	104.0×7.0 (90.0)	120.0×7.0 (106.0)	120.0×8.0 (104.0)	122.0×7.0 (108.0)	122.0×8.0 (106.0)
122.0×10.0 (102.0)	122.0×12.0 (98.0)	127.0×7.0 (113.0)	127.0×8.0 (111.0)	132.0×8.0 (116.0)	142.0×8.0 (126.0)	152.0×7.0 (138.0)	152.0×8.0 (136.0)	152.0×10.0 (132.0)	152.0×12.0 (128.0)
162.0×8.0 (146.0)									

単位：外径(mm)×肉厚(mm)
カッコ内 内径(mm)

S25C丸棒

22.0	25.0	28.0	32.0	34.0	36.0	38.0	42.0	44.0	46.0
48.0	50.0	55.0	60.0	65.0	70.0	75.0	80.0	85.0	90.0
95.0	100.0	110.0	120.0	130.0	140.0	150.0	160.0	170.0	180.0
190.0	200.0	210.0	220.0	230.0	240.0	250.0	260.0	270.0	280.0
290.0	300.0	310.0	320.0	330.0	340.0	350.0	360.0	370.0	380.0

単位：外径(mm)

S45C丸棒

19.0	22.0	25.0	28.0	32.0	34.0	36.0	38.0	42.0	44.0
46.0	48.0	50.0	55.0	60.0	65.0	70.0	75.0	80.0	85.0
90.0	95.0	100.0	110.0	120.0	130.0	140.0	150.0	160.0	170.0
180.0	190.0	200.0	210.0	220.0	230.0	240.0	250.0	260.0	270.0
280.0	290.0	300.0	310.0	320.0	330.0	340.0	350.0	360.0	370.0
380.0									

単位：外径(mm)